

LZC-TR150

桶装湿巾复卷机

LZC-TR150

Barrel wet wipes rewinder

诚信致专 卓越服务 恒久品质



技术参数 Technical specification

适用材料 Applicable materials	水刺无纺布、热风布、可降解不织布 spunlace non-woven fabric, washable, degradable materials, etc.
原布克重 Original cloth weight	35-60g/m ²
原布规格 Original fabric specifications	大卷分切, 幅宽600-1600mm, 卷径≤1200mm, 内芯3英寸 Large roll slitting, width 600-1600 mm, Roll diameter: ≤1,200 mm, Inner paper core 3 inches
放卷方式 The way to release the roll	伺服控制 Servo control
放卷速度 Volume release speed	120米/分钟 120m/min
打点距离 Dot distance	75-300mm
复卷直径 Rewinding diameter	60-230mm
切断方式 Cutting method	同步分切+点断 Synchronous slitting + point breaking
卷布控制 Roll cloth control	伺服电机 Servo motor control
打点控制 Break control	伺服电机 Servo motor control
操作界面 Operation interface	10寸液晶屏 10-inche LCD screen
卷心轴切换 Mandrel switching	三轴循环, 自动切换 Three-mandrel cycle, automatic switching
卷心轴摆放 Mandrel placement	自动摆放 Automatic placement
无纺布抽头 Non-woven fabric tap	自动抽头 Automatic pull head

电力要求 Electricity requirements	三相五线制, AC380V, 50/60Hz, 8kW Three-phase five-wire system, AC380V, 50/60 Hz, 8Kw
设备尺寸 Equipment size	长4000mm, 宽3500mm, 高2200mm length 4000 mm, width 3,500 mm, high 2,200 mm
设备重量 Equipment weight	约4500Kg Weigh 4,500 Kg

本机特点 Features of this machine

控制系统 Control system	西门子smart2000 Siemens Smart2000
折叠方式 Folding method	V型折叠, C型折叠, 或按要求定制 V.Type folding, C.Type folding, or customized as required
刮断刀快速调节 Quick adjustment of the scraping blade	通过调节可快速调刀 Through adjustment can quickly adjust the blade
快速更换点距 Quick change of point spacing	简单调节可快速更换产品 Simple adjustment can quickly replace products